

## Runxin Automatic Filter Valve

53520T(F111B1) / 53620T(F111B3)



20m<sup>3</sup> /h

Automatic Filter Valve: 53520T(F111B)

## Runxin F111B1 Automatic Filter Valve

### Technical Parameters :

- Water Pressure-----0.2—0.6MPa
- Water Temperature-----5°C-50°C
- Transformer Output-----DC24V、 1.5A
- Water Turbidity----- < 20FTU
- Inlet/Outlet-----2" Male
- Drain-----2" Male
- Base-----4"-8UN
- Riser Pipe-----2 "D-GB
- Max Flow Rate-----20 m3/h
- Suitable Tank Size (in)-----28" ~ 40"

### Product Characteristics :

- It adopts hermetic head faces with high degree pottery and corrosion resistance for opening and closing.
- LED dynamic screen display LED.The stripe on dynamic screen flash, it indicates the control valve is in service, otherwise, it is in rinse cycle.
- Having long outage indicator
- It could set up rinsing frequency
- Buttons are locked when no operation within 1 minute
- Having interlock function
- With signal output connector
- With remote handling input connector
- With pressure relief connector
- All parameters can be modified according to the need

### Range of Application :

Residential filtration system

Swimming pool filtration equipment

Active carbon or sand filter in RO pretreatment filtration system