

# Runxin Automatic Filter Valve

53540(F112B1) / 53640(F112B3)



40m<sup>3</sup> /h

**Automatic Filter Valve: 53540(F112B)**

## Runxin 40 m3/h Automatic Filter valve F112B1

### Technical Parameters :

- Water Pressure-----0.2—0.6MPa
- Water Temperature-----5°C-50°C
- Transformer Output-----DC24V、 4A
- Water Turbidity----- < 2FTU
- Inlet/Outlet-----DN65
- Drain-----DN65
- Top and Bottom Strainer -----DN80
- Max Flow Rate-----40 m3/h
- Suitable Tank Size (in)-----24" ~ 63"

### Product Characteristics :

- It adopts hermetic head faces with high degree pottery and corrosion resistance for opening and closing.
- The main valve uses the structure of four tee pistons. The distribution valve is combined with main valve.
- LED dynamic screen display LED.The stripe on dynamic screen flash, it indicates the control valve is in service, otherwise, it is in rinse cycle.
- Having long outage indicator
- It could set up rinsing frequency
- Buttons are locked when no operation within 1 minute
- With signal output connector
- With remote handling input connector
- With pressure relief connector
- All parameters can be modified according to the need

### Range of Application :

Filtration system

Swimming pool filtration equipment

Active carbon or sand filter in RO pretreatment filtration system