

Runxin Automatic Softener Valve (F63B1&F63B3)



4m³ /h

Automatic Softener Valve:63604S(F63B3)

Technical Parameters :

- Water Pressure-----0.15—0.6MPa
- Water Temperature-----5°C-50°C
- Transformer Output-----DC12V、 1.5A
- Water Turbidity-----Down-flow regeneration < 5FTU
- Inlet/Outlet-----1”M
- Drain-----1/2”M
- Brine Line Connector-----3/8”M
- Base-----2.5”-8NPSM
- Riser Pipe-----1.05 ”OD
- Max Flow Rate-----4 m3/h
- Suitable Tank Size (in)----- 6” ~ 18”

Product Characteristics :

- It adopts hermetic head faces with high degree pottery and corrosion resistance for opening and closing.
- No water pass the valve of single tank type in regeneration
- LED dynamic screen display LED.The stripe on dynamic screen flash, it indicates the control valve is in service, otherwise, it is in regeneration cycle.
- Having long outage indicator
- It can choose time clock type or meter type by program selection
- Buttons are locked when no operation within 1 minute
- Having interlock function
- With signal output connector
- With remote handling input connector
- With pressure relief connector
- All parameters can be modified according to the need

Range of Application :

Residential filtration system Ion exchange equipment
Boiler softening water system
RO pretreatment softening system, etc