

Runxin Automatic Softener Valve

63502(F65B1) / 63602(F65B3)



2m³ /h

Automatic Softener Valve:63602(F65B3)

Runxin Automatic Softener Valve F65B1

Technical Parameters :

- Water Pressure-----0.15—0.6MPa
- Water Temperature-----5°C-50°C
- Transformer Output-----DC12V、 1.5A
- Water Turbidity-----Down-flow regeneration < 5FTU
- Inlet/Outlet-----3/4" Female
- Drain-----1/2" Male
- Brine Line Connector-----3/8" Male
- Base-----2.5"-8NPSM
- Riser Pipe-----1.05 "OD
- Max Flow Rate-----2 m3/h
- Suitable Tank Size (in)----- 6" ~ 12"

Product Characteristics :

- It adopts hermetic head faces with high degree pottery and corrosion resistance for opening and closing.
- No water pass the valve of single tank type in regeneration
- LED dynamic screen display LED.The stripe on dynamic screen flash, it indicates the control valve is in service, otherwise, it is in regeneration cycle.
- Having long outage indicator
- It can choose time clock type or meter type by program selection
- Buttons are locked when no operation within 1 minute
- Having interlock function
- With signal output connector
- With remote handling input connector
- With pressure relief connector
- All parameters can be modified according to the need

Range of Application :

Residential filtration system Ion exchange equipment

Boiler softening water system

RO pretreatment softening system, etc