

Runxin Automatic Filter Valve

53504S(F67B1)



4m³ /h

Automatic Filter Valve: 53504S(F67B1)

Runxin F67B1 Automatic Filter Valve

Technical Parameters :

- Water Pressure-----0.15—0.6MPa
- Water Temperature-----5°C-50°C
- Transformer Output-----DC12V、 1.5A
- Water Turbidity----- < 20FTU
- Inlet/Outlet-----1"F
- Drain-----1"F
- Base-----2.5"-8NPSM
- Riser Pipe-----1.05 "OD
- Max Flow Rate-----4 m3/h
- Suitable Tank Size (in)-----6" ~ 14"

Product Characteristics :

- It adopts hermetic head faces with high degree pottery and corrosion resistance for opening and closing.
- No water passes the valve in rinse in single tank type.
- LED dynamic screen display LED.The stripe on dynamic screen flash, it indicates the control valve is in service, otherwise, it is in rinse cycle.
- Having long outage indicator
- It could set up rinsing frequency
- There are two kinds of time clock types: by hours or by days
- Buttons are locked when no operation within 1 minute
- Having interlock function
- With signal output connector
- With remote handling input connector
- With pressure relief connector
- All parameters can be modified according to the need

Range of Application :

Residential filtration system

Swimming pool filtration equipment

Active carbon or sand filter in RO pretreatment filtration system