

Runxin Automatic Filter Valve

53550(F96B1) / 53650(F96B3)



50m³ /h

Automatic Filter Valve: 53550(F96B)

Runxin 50 m3/h Automatic Filter valve 53550 (F96B1) 53650 (F96B3)

Technical Parameters :

- Water Pressure-----0.2—0.6MPa
- Water Temperature-----5°C-50°C
- Transformer Output-----DC24V、4A
- Water Turbidity----- < 2FTU
- Inlet/Outlet-----DN80
- Drain-----DN80
- Top and Bottom Strainer -----DN100
- Max Flow Rate-----50 m3/h
- Suitable Tank Size (in)-----24" ~ 63"

Product Characteristics :

- It adopts hermetic head faces with high degree pottery and corrosion resistance for opening and closing.
- The main valve uses the structure of four tee pistons. The distribution valve is combined with main valve.
- LED dynamic screen display LED.The stripe on dynamic screen flash, it indicates the control valve is in service, otherwise, it is in rinse cycle.
- Having long outage indicator
- It could set up rinsing frequency
- Buttons are locked when no operation within 1 minute
- With signal output connector
- With remote handling input connector
- With pressure relief connector
- All parameters can be modified according to the need

Range of Application :

Filtration system

Swimming pool filtration equipment

Active carbon or sand filter in RO pretreatment filtration system